

HY-DRIVE SPECIFICATIONS

PUMPING FLOW VS. PUMPING HEIGHT

PUMP	Item UPC	Nominal	Watts	Amps	at 0'	at 1'	at 3'	at 5'	at 7'	at 10'	at 15'	at 20'	at 25'	at 30'	Shutoff
1900	20210	1900	93	.78	1910	1710	1325	870	555	-	-	-	-	-	10
2550	20215	2550	147	1.25	2505	2380	2010	1490	1045	455	-	-	-	-	11.5
4850*	20220	4850	328	3.00	4850	4725	4300	3700	3050	2225	1550	300	-	-	22.5
6100*	20225	6100	520	4.39	6100	5750	4725	4175	3450	2400	1625	850	250	-	28
6600*	20230	6600	593	4.94	6625	6600	6275	5500	4925	4325	3325	2425	1850	550	30.5

All Pumps Listed Above Have 1-1/2" MPT Outlets

**To Achieve Maximum Flow from 4850, 6100 and 6600 GPH Pumps, a Minimum of 2" ID Tubing Must Be Used*



- 1 Integral Pre-Filter**
- 2 Impeller Cover with Threaded Inlet/Outlet**
- 3 Directional Impeller Improves Pumping Capacity**
- 4 Stainless Steel Rotor**
- 5 Convenient Handle**
- 6 Energy Saving Motor Design**
- 7 Sturdy Base with Mounting Holes**