

BBF XS SPECIFICATIONS

- Proven product with over 20 years in the field
- Provides biological and mechanical filtration
- Uses low pressure, low horsepower pump
- Easy to install, with or without an UV
- Weather and salt resistant
- Small compact footprint
- Excellent nitrification

Polyethylene Units



| MODELS | Max Flow Rate(gpm) | Cubic Feet Bead Media | Height / diameter (in) | Inlet and Outlet Sizes (in) | Backwash Water Loss (gallons) |
|---------|--------------------|-----------------------|------------------------|-----------------------------|-------------------------------|
| XS300 | 10 | .25 | 20 / 12 | 3/4" | 2.5 |
| XS500 | 10 | .25 | 32/10 | 3/4" | 5 |
| XS1000 | 10 | .5 | 35/12 | 1" | 8.5 |
| XS2000 | 15 | 1 | 42.5/16 | 1 1/2" | 12 |
| XS4000 | 30 | 2 | 49/19.5 | 1 1/2" | 25 |
| XS6000 | 45 | 3 | 49/19.5 | 1 1/2" | 25 |
| XS8000 | 60 | 4 | 60/26 | 2" | 45 |
| XS10000 | 75 | 5 | 60/26 | 2" | 45 |

XS models have a max pressure of 10 psi. XS models are manufactured out of polyethylene plastic.